

## Technical Data Sheet (TDS):

### Specifications

|                          |            |                      |                                                                                                                             |
|--------------------------|------------|----------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Model:                   | ST-RX-C088 | Power:               | 14W <small>The longest connection is 5m/9W,<br/>and the longest connection is 20m</small>                                   |
| Light Source:            | Bridgelux  | Input Voltage:       | DC24V                                                                                                                       |
| Colour Rendering Index:  | Ra≥90      | Main Material:       | Aluminium                                                                                                                   |
| Driver:                  | Remote     | Installation Method: | Surface Mounted                                                                                                             |
| Luminaire Luminous Flux: | Lumen      | Luminous Efficiency: | Lumen/W                                                                                                                     |
| Structure:               | Fixed      | Beam Angle:          | /                                                                                                                           |
| IP Rating:               | IP 20      | Colour Temperature:  | <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 3500K <input type="checkbox"/> 4000K |
| Dimensions:              | 8.5*17mm   | Cutout:              | /                                                                                                                           |
| Insulation Class:        | Class 3    | Optics Accessories:  | —                                                                                                                           |

Intelligent Control: ☐ (Non-Dim) ☐ (Triac) ☐ DALI ☐ 0-10V ☐ PWM ☐ DMX512

Finish: Bending method: side bending, outlet method: straight outlet, cutting length: one lamp one cut/side bend, rearfeed, one cut at any length