

Technical Data Sheet (TDS):

| Specifications           |                                                                                                                                                                                               |                      |                                                                                                                                                            |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model:                   | ST-DG26                                                                                                                                                                                       | Power:               | 28W                                                                                                                                                        |
| Light Source:            | Luminus                                                                                                                                                                                       | Input Voltage:       | AC220~240V,50/60Hz                                                                                                                                         |
| Colour Rendering Index:  | Ra≥95                                                                                                                                                                                         | Main Material:       | Aluminium                                                                                                                                                  |
| Driver:                  | Remote                                                                                                                                                                                        | Installation Method: | track mounted                                                                                                                                              |
| Luminaire Luminous Flux: | 2931 Lumen                                                                                                                                                                                    | Luminous Efficiency: | 122 Lumen/W                                                                                                                                                |
| Structure:               | Adjustable angle                                                                                                                                                                              | Beam Angle:          | <input type="checkbox"/> 10° <input type="checkbox"/> 15° <input type="checkbox"/> 24° <input type="checkbox"/> 36°                                        |
| IP Rating:               | IP 20                                                                                                                                                                                         | Colour Temperature:  | <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 3500K <input type="checkbox"/> 4000K <input type="checkbox"/> 5700K |
| Dimensions:              | Ø88*155mm                                                                                                                                                                                     | Cutout:              | /                                                                                                                                                          |
| Insulation Class:        | Class 3                                                                                                                                                                                       | Optics Accessories:  | —                                                                                                                                                          |
| Intelligent Control:     | <input type="checkbox"/> (Non-Dim) <input type="checkbox"/> (Triac) <input type="checkbox"/> DALI <input type="checkbox"/> 0-10V <input type="checkbox"/> PWM <input type="checkbox"/> DMX512 |                      |                                                                                                                                                            |
| Finish:                  | <input type="checkbox"/> WH <input type="checkbox"/> BK                                                                                                                                       |                      |                                                                                                                                                            |

Photometric and Luminous Intensity Distribution Curve

